

BOISE, ID ATLANTA, GA

### **Profile Description:**

Manufactured to create a modern vertical design element with a 1/2" reveal that captures the edges of 5/16" fiber cement panels as they transition to 5/16" lap siding planks. Providing a clean and modern aesthetic along with protection for panel and plank edges. If used in a horizontal application, do not install in a manner where the aesthetic flange can accumulate moisture.


## **Alternative Vertical Design Options**







# FbC-T-Reveal Vert TR



Material Length 10' (120")

Material Composition 6063 T5

Standard Finishes Field Paintable

Powder Coated Clear Anodized

# **Field Painting Instructions**

Orsted provides a high-quality coating designed to accept direct-to-metal, acrylic, and latex paint. Aluminum should be free of dirt, oil, and other contaminants that can compromise paint adhesion. Reference best practices for further instructions.

### Western USA

Patrick O'Neill 404.376.0243 patrick@orstedusa.com 6779 W. Targee St. Boise, ID 83709



#### **Cutting Instructions**

Orsted recommends using full-length material when field conditions allow, minimizing abutting joints. To achieve a high-quality cut, use a non-ferrous carbide blade with a high tooth count (90+) along with commercial grade equipment. Reference best practices for further instructions.

## **Eastern USA**

Jonathan Kurtz 404.431.9605 jonathan@orstedusa.com 2272 Mabros Ind. Pkwy. Ellenwood, GA 30294